

---

# Runners Documentation

*Release latest*

Jan 29, 2022



# CONTENTS

<b>1 Podman Gitlab Runner</b>	<b>1</b>
<b>2 Docker Gitlab Runner</b>	<b>3</b>



## PODMAN GITLAB RUNNER

First you need to run: - I am using volume to store gitlab runner config, if u want to can mount a simple directory. You have to mount to this point: “/etc/gitlab-runner”

- Mount volume: `-v podman-gitlab-runner-1:/etc/gitlab-runner`
- Mount directory: `-v /opt/gitlab-runner:/etc/gitlab-runner`
- Gitlab executor always have to set to shell! - **DO NOT CHANGE IT!**

```
podman run -d --privileged --name CONTAINER_NAME -v PODMAN_SOCKET:/run/podman/podman.sock -v YOUR_VOLUME_or_DIR:/etc/gitlab-runner adamkoro/podman-gitlab-runner:latest
```

Register to Gitlab:

```
podman exec -it CONTAINER_NAME gitlab-runner register -n --url GIT_URL --registration-token=YOUR_TOKEN --executor shell --description "YOUR_DESC" --tag-list "YOUR_TAGS"
```

Implement in CD/CD

When you are implemeting in CI/CD, you have to set **podman-remote** instead of podman in “script” section.



## DOCKER GITLAB RUNNER